



TR 2.36 C5 PORTABLE POWER

WATERPUMPRangeAQUALINE INTENS

PRODUCT ADVANTAGES

HONDA Professional Engine Resistant pump-barrel Automatic priming Easy acces to the turbine Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

STAGE V (2016/1628 EU): This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE INTENS

Designed for water with low solid content.

TR 2.36 C5

GENERAL SPECIFICATIONS

| Range | AQUALINE INTENS |
|--|-------------------------------------|
| Type liquid | Heavily sedimented water pump |
| Suction diameter [mm] | 50 |
| Backflow diameter (mm) | 50 |
| Outflow maximum (L/min) | 600 |
| Outlflow maximum (m3/h) | 36 |
| Lifting height (m) | 29 |
| Suction height (m) | 8 |
| Granulometry (mm) | 8 |
| Automatic priming | Oui |
| Fuel | Petrol |
| Tank (L) | 2 |
| 75% cons. (I/h) | 1 |
| 75% Autonomy (h) | 2 |
| Sound power level guaranteed LwA dB(A) | 103 |
| Acoustic pressure level @1m in dB(A) | 87 |
| Acoustic pressure level @7m in dB(A) | 72 |

ENGINE SPECIFICATIONS

| Engine brand | HONDA |
|---|----------|
| Engine ref. | GX120_C5 |
| Engine Type | O.H.V. |
| Start | Starter |
| Oil shutdown | Oui |
| Displacement (cm3) | 118 |
| Oil system capacity including filters (I) | 0.6 |

DIMENSIONS AND WEIGHT

| Length (cm) | 46,8 |
|-----------------|------|
| Width (cm) | 36,2 |
| Height (cm) | 39,8 |
| Dry Weight (kg) | 23 |

PACKAGING

| Packaging type | Box |
|------------------------------------|--------|
| Length (cm) | 48 |
| Width (cm) | 38 |
| Height (cm) | 41,5 |
| Weight (kg) | 26,5 |
| Pallet type | 120/80 |
| Number of box by pallet | 12 |
| Pallet height (cm) | 138 |
| weight of the packaged Pallet (kg) | 328 |



















KOHLE



ACCESSORIES SUPPLIED

Inlet filter Circlips Screw-on connectors User and maintenance manual

OPTIONS

| RBH1 | RBH1 - Box of 20 cans of 1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE |
|--------|---|
| RBH0-5 | RBHO-5 - Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE |
| RHO | RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm |
| R11 | R11 - Piping kit for 2 water pumps made up of 5m suction + 25m lift |
| R13 | R13 - Rapid connections kit for 2 water pumps |