



## TRASH 4 C5

PORTABLE POWER

WATERPUMP Range AQUALINE SPECIALIST

### PRODUCT ADVANTAGES

- KOHLER air-cooled industrial engine
- Resistant pump-barrel
- Automatic priming
- Easy access to the turbine
- Offers accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

### Range AQUALINE SPECIALIST

High performance under extreme conditions.



## TRASH 4 C5

### GENERAL SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	Extremely heavily sedimented water pump
Suction diameter [mm]	100
Backflow diameter (mm)	100
Outflow maximum (L/min)	1600
Outflow maximum (m3/h)	96
Lifting height (m)	17
Suction height (m)	8
Granulometry (mm)	20
Automatic priming	Oui
Fuel	Diesel Fuel
Tank (L)	4,3
75% cons. (l/h)	1,4
75% Autonomy (h)	3,1
Sound power level guaranteed LwA dB(A)	110
Acoustic pressure level @1m in dB(A)	95
Acoustic pressure level @7m in dB(A)	81

### ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	KD350_C5
Engine Type	Diesel O.H.V.
Start	Starter
Oil shutdown	Non
Displacement (cm3)	349
Oil system capacity including filters (l)	1,2

### DIMENSIONS AND WEIGHT

Length (cm)	71,5
Width (cm)	57
Height (cm)	59
Dry Weight (kg)	90

### PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	59,5
Weight (kg)	102
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	132
weight of the packaged Pallet (kg)	418

### ACCESSORIES SUPPLIED

Inlet filter  
Circlips  
Fast connections  
User and maintenance manual

### OPTIONS

- RKB2** RKB2 - Trolley kit for HX 4000 - 6000 – 7500T / HXC 4000 - 6000 – 7500T / TECHNIC 10000 -15000 / VX 200/4 -220-7,5 / WELDARC 300 / TRASH ; Puncture-proof wheels Ø 290 mm
- RH1** RH1 - Protective cover for HX 4000 – 6000 – 7500T / HXC 4000 – 6000 – 7500T / PERFORM 4500 – 4500 XL – 5500T – 5500 T XL – 6500 – 6500 XL – 7500 T – 7500 XL / TECHNIC 6500 – 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm
- R21** R21 - Pipe kit for 4P pumps with 3 m of suction + 25 m discharge piping