KOHLER



TR 3.60 C5

PORTABLE POWER

WATERPUMPRangeAQUALINE INTENS

PRODUCT ADVANTAGES

HONDA Professional Engine Resistant pump-barrel Automatic priming Easy acces to the turbine Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range AQUALINE INTENS Designed for water with low solid content.



TR 3.60 C5

GENERAL SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Heavily sedimented wateı pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	900
Outlflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Oui
Fuel	Petrol
Tank (L)	3,1
75% cons. (l/h)	0,9
75% Autonomy (h)	3,4
Sound power level guaranteed LwA dB(A)	105
Acoustic pressure level @1m in dB(A)	91
Acoustic pressure level @7m in dB(A)	76
_	

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (I)	0,6

DIMENSIONS AND WEIGHT L

Length (cm)	50,5
Width (cm)	39,8
Height (cm)	46,6
Dry Weight (kg)	29

PACKAGING

Packaging type	Box
Length (cm)	51,5
Width (cm)	42
Height (cm)	48
Weight (kg)	34,5
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	157
weight of the packaged Pallet (kg)	424



14 janv.. 24

TR 3.60 C5 - PORTABLE POWER - WATERPUMP AQUALINE INTENS This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528. SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France – portable.kohlerpower.com



ACCESSORIES SUPPLIED

Inlet filter Circlips Screw-on connectors User and maintenance manual

OPTIONS

RBH1	RBH1 - Box of 20 cans of 1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE
RBH0-5	RBHO-5 - Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE
RHO	RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm
R12	R12 - Piping kit for 3 water pumps made up of 5 m suction + 25 m lift

R14 R14 - Rapid connections kit for 3 water pumps

