

HP 2.26 C5

EAN 3499231002940



PRODUCT ADVANTAGES

HONDA Professional Engine

Automatic priming

Solid and high-performance equipment

Offers accessories

High-pressure equipment

With nearly 6 bar of pressure, the HP 2.26 H can be used for high-pressure cleaning of machinery, such as agricultural vehicles. When combined with the nozzle kit, it can be used to suppress fires.

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range

AQUALINE SPECIALIST

High performance under extreme conditions.

Fuel Petrol

Granulometry (mm) 8

Type liquid High pressure use

Lifting height (m) 57

Outflow maximum (m3/h) 26,4

75% Autonomy (h) 3,4

Sound power level guaranteed LwA dB(A) 108

Dimensions L x W x H (cm) | Weight (kg) 41,5 x 42 x 45,5 | 30

HP 2.26 C5 - WATER PUMP - AQUALINE SPECIALIST - 6 février 2026

portable.rehlko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.



SDMO Industries
accredited testing laboratory ISO 17025
n°1-2171
scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	AQUALINE SPECIALIST
Type liquid	High pressure use
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (m3/h)	26,4
Outflow maximum (L/min)	440
Lifting height (m)	57
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Oui
Fuel	Petrol
Tank (L)	3,1
75% cons. (l/h)	0,9
75% Autonomy (h)	3,4
Sound power level guaranteed LwA dB(A)	108
Acoustic pressure level @1m in dB(A)	92
Acoustic pressure level @7m in dB(A)	77



ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (l)	0,6



DIMENSIONS AND WEIGHT

Length (cm)	41,5
Width (cm)	42
Height (cm)	45,5
Dry Weight (kg)	30



PACKAGING

Packaging type	Box
Length (cm)	54
Width (cm)	42
Height (cm)	45
Weight (kg)	35
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	148
weight of the packaged Pallet (kg)	430

ACCESSORIES SUPPLIED



Inlet filter
Circlips
Screw-on connectors
User and maintenance manual

Additional equipment



3499231921463

RKS13 - Maintenance kit for ST 2.38 / ST 3.60/ TR 2.35 / TR 2.60 / HP 2.26 / XT 3.78 including oil, spark plug and air filter



3499231036006

GENLUB 15W40 1L - Oil can 1L (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



3499231035009

GENLUB 15W40 0.5L - Oil can 0.5L (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



RHO

RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm



R09

R09 - Fire-fighting kit for HP 2.26 H pumps with 2 fire hose connectors, 25 m fire hose, 5 m intake hose and fire lance
