

# TECHNIC 10000 A C5

EAN 3499231003213



## PRODUCT ADVANTAGES

Generating set guaranteed 3 years  
 KOHLER air-cooled industrial engine  
 Electric starter with batteries without maintenance  
 Large Autonomy  
 Connection interface equipped with an hour meter and the APM202 control unit  
 The GENERATOR SMART CARE is a Bluetooth box combined with a smartphone application that can be adapted to all the brand's portable generators and enables maintenance to be tracked.  
 STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

## Range

TECHNIC

A long run time equipment that can withstand extreme conditions, for daily professional use.

Fuel Petrol

Nominal voltage (V) | Number of Phase 230 | Single phase

Max power (kW) 10,3 kW

75% Autonomy (h) 7

Sound power level guaranteed LwA dB(A) 97

Dimensions L x W x H (cm) | Weight (kg) 89,5 x 58,5 x 77 | 163



TECHNIC 10000 A C5 - GENERATING SET - TECHNIC - 6 février 2026

[portable.rehlko.com](http://portable.rehlko.com)

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.



SDMO Industries  
 accredited testing laboratory ISO 17025  
 n°1-2171  
 scope available on [www.cofrac.fr](http://www.cofrac.fr)





## GENERAL SPECIFICATIONS

<b>Range</b>	TECHNIC
<b>Frequency (Hz)</b>	50 Hz
<b>Max power (kW)</b>	10,3
<b>Nominal voltage (V)</b>	230
<b>Number of Phase</b>	Single phase
<b>Assigned current (A)</b>	36,5
<b>Fuel</b>	Petrol
<b>Tank (L)</b>	35
<b>75% cons. (l/h)</b>	5
<b>75% Autonomy (h)</b>	7
<b>Sound power level guaranteed LwA dB(A)</b>	97
<b>Acoustic pressure level @1m in dB(A)</b>	83
<b>Acoustic pressure level @7m in dB(A)</b>	69



## ENGINE SPECIFICATIONS

<b>Engine brand</b>	REHLKO
<b>Engine ref.</b>	CH680_C5
<b>Start</b>	Electrical
<b>Oil shutdown</b>	Oui
<b>Displacement (cm3)</b>	670
<b>Oil system capacity including filters (l)</b>	1,9



## ALTERNATOR SPECIFICATION

<b>Technology</b>	Brushless
<b>AVR Regulation</b>	No
<b>Indication of protection</b>	IP 23
<b>Insulation class</b>	H



## PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 230V 32A socket - circuit breaker + hour meter + indicator + APM202



## DIMENSIONS AND WEIGHT

<b>Length (cm)</b>	89,5
<b>Width (cm)</b>	58,5
<b>Height (cm)</b>	77
<b>Dry Weight (kg)</b>	163



## PACKAGING

<b>Packaging type</b>	Box / Pallet
<b>Length (cm)</b>	91
<b>Width (cm)</b>	58,5
<b>Height (cm)</b>	92
<b>Weight (kg)</b>	180
<b>Pallet type</b>	
<b>Number of box by pallet</b>	0
<b>Pallet height (cm)</b>	0
<b>weight of the packaged Pallet (kg)</b>	0

## ACCESSORIES SUPPLIED



Funnel  
User and maintenance manual  
Battery without maintenance  
Hour meter

## Additional equipment



**3499231002834** RSTART2 - Wireless remote control with on/off button. Requires a genset fitted with an APM202/APM303

---



**R05M** R05M - Manual transfer switch for connecting a single-phase generator to a house

---



**RKB2** RKB2 - Trolley kit for HX 4000 - 6000 – 7500T / HXC 4000 - 6000 – 7500T / TECHNIC 10000 -15000 / VX 200/4 -220-7,5 / WELDARC 300 / TRASH ; Puncture-proof wheels Ø 290 mm

---



**3499231920060** RKS5 - Maintenance kit for TECHNIC 10000 - 15000 / WELDARC 300 TE XL including oil, spark plug, oil filter and air filter

---



**3499231002827** RAP - Adapter from 16A industrial socket to 10/16A domestic socket

---



**RH2** RH2 - Protective cover for TECHNIC 10000 – 15000 / DIESEL 10000 A XL STAND BY – 15000 TA XL ; Dimensions : 91 x 58 x 56 cm

---



**RPM** RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket

---



**RPQ** RPQ - 1m earth spike, supplied with 2m 10mm<sup>2</sup> mains cable

---