

TECHNIC 15000TA AVR C5

EAN 3499231003244



PRODUCT ADVANTAGES

Generating set guaranteed 3 years
 KOHLER air-cooled industrial engine
 Electric starter with batteries without maintenance
 Large Autonomy
 Connection interface equipped with an hour meter and the APM202 control unit
 The GENERATOR SMART CARE is a Bluetooth box combined with a smartphone application that can be adapted to all the brand's portable generators and enables maintenance to be tracked.
 The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature

Range

TECHNIC

A long run time equipment that can withstand extreme conditions, for daily professional use.

Fuel Petrol

Nominal voltage (V) | Number of Phase 400 | Three phase

Max power (kW) | Max power (kVA) 11,5 kW | 14,4 kVA

75% Autonomy (h) 7

Sound power level guaranteed LwA dB(A) 97

Dimensions L x W x H (cm) | Weight (kg) 89,5 x 58,5 x 77 | 172



TECHNIC 15000TA AVR C5 - GENERATING SET - TECHNIC - 6 février 2026

portable.rehlko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

*This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.*



SDMO Industries
 accredited testing laboratory ISO 17025
 n°1-2171
 scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	TECHNIC
Frequency (Hz)	50 Hz
Max power (kW)	11,5
Max power (kVA)	14,4
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Assigned current (A)	13,3
Tank (L)	35
75% cons. (l/h)	5
75% Autonomy (h)	7
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69



ENGINE SPECIFICATIONS

Engine brand	REHLKO
Engine ref.	CH680_C5
Start	Electrical
Oil shutdown	Oui
Displacement (cm3)	670
Oil system capacity including filters (l)	1,9



ALTERNATOR SPECIFICATION

Technology	Collar and brush
AVR Regulation	Yes
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter + indicator + APM202



DIMENSIONS AND WEIGHT

Length (cm)	89,5
Width (cm)	58,5
Height (cm)	77
Dry Weight (kg)	172



PACKAGING

Packaging type	Box / Pallet
Length (cm)	91
Width (cm)	58,5
Height (cm)	92
Weight (kg)	186
Pallet type	
Number of box by pallet	0
Pallet height (cm)	0
weight of the packaged Pallet (kg)	0

ACCESSORIES SUPPLIED



Funnel
 Funnel
 Battery without maintenance
 Hour meter

Additional equipment



3499231002834 RSTART2 - Wireless remote control with on/off button. Requires a genset fitted with an APM202/APM303



VERSO10T40A The manual changeover switch is used to connect and disconnect a 3-phases generating set manually to a domestic circuit when there is a power cut.



RKB2 RKB2 - Trolley kit for HX 4000 - 6000 – 7500T / HXC 4000 - 6000 – 7500T / TECHNIC 10000 -15000 / VX 200/4 -220-7,5 / WELDARC 300 / TRASH ; Puncture-proof wheels Ø 290 mm



3499231920060 RKS5 - Maintenance kit for TECHNIC 10000 - 15000 / WELDARC 300 TE XL including oil, spark plug, oil filter and air filter



3499231002827 RAP - Adapter from 16A industrial socket to 10/16A domestic socket



RH2 RH2 - Protective cover for TECHNIC 10000 – 15000 / DIESEL 10000 A XL STAND BY – 15000 TA XL ;
Dimensions : 91 x 58 x 56 cm



RPM RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket



RPQ RPQ - 1m earth spike, supplied with 2m 10mm² mains cable
