

# VX 200/4 C5

EAN 3499231003275



## PRODUCT ADVANTAGES

HONDA Professional Engine  
 Generating set guaranteed 3 years  
 Light storage box integrated  
 Solid and high-performance equipment  
 Auxiliary Single phase output  
 STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

## Range

WELDARC INTENS  
 Welding sets which can be used on sites where there is no electricity.

Fuel Petrol

Nominal voltage (V) | Number of Phase 230 | Single phase

Normal duty cycle 35% (A) 200 A

Rods diameter maxi (mm) 4

75% Autonomy (h) 2,4

Sound power level guaranteed LwA dB(A) 96

Dimensions L x W x H (cm) | Weight (kg) 88 x 58,5 x 55,5 | 87



VX 200/4 C5- WELDING SET - WELDARC INTENS - 6 février 2026

[portable.rehlko.com](http://portable.rehlko.com)

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.



SDMO Industries  
 accredited testing laboratory ISO 17025  
 n°1-2171  
 scope available on [www.cofrac.fr](http://www.cofrac.fr)





## GENERAL SPECIFICATIONS

<b>Range</b>	WELDARC INTENS
<b>Frequency (Hz)</b>	50 Hz
<b>Max power (kW)</b>	4
<b>Max power (kVA)</b>	4
<b>Normal duty cycle 35% (A)</b>	200
<b>Intensif duty cycle 60% (A)</b>	170
<b>Stricking volts (V)</b>	75
<b>Rods diameter mini (mm)</b>	1.6
<b>Rods diameter maxi (mm)</b>	4
<b>Nominal voltage (V)</b>	230
<b>Number of Phase</b>	Single phase
<b>Fuel</b>	Petrol
<b>Tank (L)</b>	6,1
<b>75% cons. (l/h)</b>	2,5
<b>75% Autonomy (h)</b>	2,4
<b>Sound power level guaranteed LwA dB(A)</b>	96
<b>Acoustic pressure level @1m in dB(A)</b>	82
<b>Acoustic pressure level @7m in dB(A)</b>	68



## ENGINE SPECIFICATIONS

<b>Engine brand</b>	HONDA
<b>Engine ref.</b>	GX390_C5
<b>Start</b>	Starter
<b>Oil shutdown</b>	Oui
<b>Displacement (cm3)</b>	389
<b>Oil system capacity including filters (l)</b>	1,1



## ALTERNATOR SPECIFICATION

<b>Technology</b>	Collar and brush
<b>AVR Regulation</b>	No
<b>Indication of protection</b>	IP 23
<b>Insulation class</b>	H



## PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker



## DIMENSIONS AND WEIGHT

<b>Length (cm)</b>	88
<b>Width (cm)</b>	58,5
<b>Height (cm)</b>	55,5
<b>Dry Weight (kg)</b>	87



## PACKAGING

<b>Packaging type</b>	Box / Pallet
<b>Length (cm)</b>	88
<b>Width (cm)</b>	58,5
<b>Height (cm)</b>	70
<b>Weight (kg)</b>	100
<b>Pallet type</b>	
<b>Number of box by pallet</b>	
<b>Pallet height (cm)</b>	
<b>weight of the packaged Pallet (kg)</b>	

## ACCESSORIES SUPPLIED



Storage box  
User and maintenance manual

## Additional equipment



**RKB2**

RKB2 - Trolley kit for HX 4000 - 6000 – 7500T / HXC 4000 - 6000 – 7500T / TECHNIC 10000 -15000 / VX 200/4 -220-7,5 / WELDARC 300 / TRASH ; Puncture-proof wheels Ø 290 mm



**R10**

R10 - Welding kit includes 1x10 m of cable, 1 earth clip, 1 electrode holder, 1 hammer, 1 brush and 1 mask (connectors not supplied).



**3499231033203**

R19 - Maintenance kit for HX 6000 - 7500 T / VX 200/4 including oil, spark plug and air filter



**RBH1**

RBH1 - Box of 20 cans of 1L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



**RBH0-5**

RBH0-5 - Box of 24 cans of 0.5L oil (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



**RH2**

RH2 - Protective cover for TECHNIC 10000 – 15000 / DIESEL 10000 A XL STAND BY – 15000 TA XL ; Dimensions : 91 x 58 x 56 cm



**RPQ**

RPQ - 1m earth spike, supplied with 2m 10mm<sup>2</sup> mains cable



**RKD1**

RKD1 - Kit of 2 removable differential adaptors for domestic sockets 16A



**3499231920831**

GSC - Generator Smart Care : Bluetooth box which can be used on all portable generator

