

PERFORM 5500 T C5

EAN 3499231003640



PRODUCT ADVANTAGES

Compact frame with protection panels against shocks
 Starting up facilitated thanks to the summer/winter positions
 KOHLER air-cooled industrial engine
 Good value for money
 Generating set guaranteed 3 years
 QUAD CLEAN AIR FILTER The Cyclonic Quad Clean air filters provide 4 levels of filtration which effectively filter out large particles and capture the finest particles. They ensure a continuous supply of clean air to the engine, fuel economies, increase the engine performance and extend its lifetime
 STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range

PERFORM

An efficient, cost effective and easy to handle equipment, suitable for frequent use.

Fuel Petrol

Nominal voltage (V) | Number of Phase 400 | Three phase

Max power (kW) | Max power (kVA) 4,5 kW | 5,6 kVA

75% Autonomy (h) 4,3

Sound power level guaranteed LwA dB(A) 97

Dimensions L x W x H (cm) | Weight (kg) 71 x 58 x 49 | 73,5



PERFORM 5500 T C5 - GENERATING SET - PERFORM - 6 février 2026

portable.rehlko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.



SDMO Industries
 accredited testing laboratory ISO 17025
 n°1-2171
 scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	PERFORM
Frequency (Hz)	50 Hz
Max power (kW)	4,5
Max power (kVA)	5,6
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Assigned current (A)	4,6
Tank (L)	7,3
75% cons. (l/h)	1,7
75% Autonomy (h)	4,3
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	82
Acoustic pressure level @7m in dB(A)	68




ENGINE SPECIFICATIONS

Engine brand	REHLKO
Engine ref.	CH395_C5
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	277
Oil system capacity including filters (l)	1,1



ALTERNATOR SPECIFICATION

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker



DIMENSIONS AND WEIGHT

Length (cm)	71
Width (cm)	58
Height (cm)	49
Dry Weight (kg)	73,5



PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	49,5
Weight (kg)	75,5
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	162
weight of the packaged Pallet (kg)	463

ACCESSORIES SUPPLIED



Funnel
 User and maintenance manual
 Floor maintaining slot
 Ergonomic handle grip

Additional equipment



3499231004012 VERSO 10 T 40A - Manual source inverter for connecting a three-phase generator to a house



3499231002575 RKB1HD - Trolley kit for PERFORM / PERFORM XL / TECHNIC 6500 - 7500T / DIESEL / WELDARC 200 - 220 ; Puncture-proof wheels Ø 290 mm



3499231920039 RKS2 - Maintenance kit for PERFORM 4500 - 5500T – 6500 - 7500 T / WELDARC 200 - 220 T including oil, spark plug and air filter



RH1 RH1 - Protective cover for HX 4000 – 6000 – 7500T / HXC 4000 – 6000 – 7500T / PERFORM 4500 – 4500 XL – 5500T – 5500 T XL – 6500 – 6500 XL – 7500 T – 7500 XL / TECHNIC 6500 – 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm



RPM RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket



RPQ RPQ - 1m earth spike, supplied with 2m 10mm² mains cable



3499231920831 GSC - Generator Smart Care : Bluetooth box which can be used on all portable generator

RRB4 retention bin
