



more information



PRESTIGE 3000 C5

PORTABLE POWER

GENERATING SET Range PRESTIGE

PRODUCT ADVANTAGES

Generating set guaranteed 3 years

KOHLER air-cooled industrial engine

Large Autonomy

Soundproofing and against shocks panels

Solid and high-performance equipment

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range PRESTIGE

Top of the range equipment that is efficient and with low noise emissions, for a wide range of standard requirements.



PRESTIGE 3000 C5

GENERAL SPECIFICATIONS

Range	PRESTIGE
Frequency (Hz)	50 Hz
Max power (kW)	2,8
Nominal voltage (V)	230
Number of Phase	Single phase
Fuel	Petrol
Tank (L)	12
75% cons. (l/h)	1,3
75% Autonomy (h)	9,2
Sound power level guaranteed LwA dB(A)	94
Acoustic pressure level @1m in dB(A)	79
Acoustic pressure level @7m in dB(A)	65

ENGINE SPECIFICATIONS

Engine brand	KOHLER
Engine ref.	CH270_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm ³)	208
Oil system capacity including filters (l)	0,6

ALTERNATOR SPECIFICATION

Technology	Brushless
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	57
Width (cm)	45
Height (cm)	46
Dry Weight (kg)	50

PACKAGING

Packaging type	Box
Length (cm)	58
Width (cm)	47
Height (cm)	47
Weight (kg)	52
Pallet type	140/110
Number of box by pallet	15
Pallet height (cm)	154
weight of the packaged Pallet (kg)	796



PRESTIGE 3000 C5

ACCESSORIES SUPPLIED

User and maintenance manual

OPTIONS

R05M R05M - Manual source inverter for connecting a single-phase generator to a house

R06 R06 - Trolley kit for HX 3000 / HXC 3000 / PRESTIGE 3000 ; Puncture-proof wheels Ø 187 mm

3499231001516 R30 - Maintenance kit for PRESTIGE 3000 including oil, spark plug and air filter

RHO RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm

RPM RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket

RPQ RPQ - 1m earth spike, supplied with 2m 10mm² mains cable

RKD1 RKD1 - Kit of 2 removable differential adaptors for domestic sockets 16A