

TECHNIC 7500 TE AVR C5

EAN 3499231003893



PRODUCT ADVANTAGES

Generating set guaranteed 3 years
 KOHLER air-cooled industrial engine
 Connection interface equipped with an hour meter
 Electric starter with batteries without maintenance
 AVR : Automatic tension regulation
 The GENERATOR SMART CARE is a Bluetooth box combined with a smartphone application that can be adapted to all the brand's portable generators and enables maintenance to be tracked.
 AVR By regulating the voltage electronically by $\pm 2\%$, depending on the model, the AVR eliminates all risk of damage to boilers or certain kinds of electronic equipment.

Range

TECHNIC

A long run time equipment that can withstand extreme conditions, for daily professional use.

Fuel Petrol

Nominal voltage (V) | Number of Phase 400 | Three phase

Max power (kW) | Max power (kVA) 6,5 kW | 8,1 kVA

75% Autonomy (h) 6,9

Sound power level guaranteed LwA dB(A) 99

Dimensions L x W x H (cm) | Weight (kg) 81 x 56,5 x 59 | 108,5



Attested NB 3065

TECHNIC 7500 TE AVR C5 - GENERATING SET - TECHNIC - 6 février 2026

portable.rehlko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.



SDMO Industries
 accredited testing laboratory ISO 17025
 n°1-2171
 scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	TECHNIC
Frequency (Hz)	50 Hz
Max power (kW)	6,5
Max power (kVA)	8,1
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Assigned current (A)	7,5
Tank (L)	18
75% cons. (l/h)	2,6
75% Autonomy (h)	6,9
Sound power level guaranteed LwA dB(A)	99
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69



ENGINE SPECIFICATIONS

Engine brand	REHLKO
Engine ref.	CH440E_C5
Start	Electrical Starter
Oil shutdown	Oui
Displacement (cm3)	429
Oil system capacity including filters (l)	1,3



ALTERNATOR SPECIFICATION

Technology	Collar and brush
AVR Regulation	Yes
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter



DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	56,5
Height (cm)	59
Dry Weight (kg)	108,5



PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56,5
Height (cm)	60
Weight (kg)	110,5
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	673

ACCESSORIES SUPPLIED



Funnel
 User and maintenance manual
 Floor maintaining slot
 Ergonomic handle grip
 Battery without maintenance

Additional equipment



3499231004012 VERSO 10 T 40A - Manual source inverter for connecting a three-phase generator to a house



3499231002575 RKB1HD - Trolley kit for PERFORM / PERFORM XL / TECHNIC 6500 - 7500T / DIESEL / WELDARC 200 - 220 ; Puncture-proof wheels Ø 290 mm



3499231005057 RKS7 - Maintenance kit for PERFORM 4500 XL - 5500T XL - 6500 XL - 7500T XL / TECHNIC 6500 - 7500T including oil, spark plug, fuel filter and air filter



RH1 RH1 - Protective cover for HX 4000 – 6000 – 7500T / HXC 4000 – 6000 – 7500T / PERFORM 4500 – 4500 XL – 5500T – 5500 T XL – 6500 – 6500 XL – 7500 T – 7500 XL / TECHNIC 6500 – 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm



RPM RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket



RPQ RPQ - 1m earth spike, supplied with 2m 10mm² mains cable
