

HX 7500 T C5

EAN 3499231004098



PRODUCT ADVANTAGES

Solid and high-performance equipment
Generating set guaranteed 3 years
HONDA Professional Engine

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range

INTENS

Equipment that is robust, long-lasting and simple to use for repetitive operations in difficult conditions.

Fuel Petrol

Nominal voltage (V) | Number of Phase 400 | Three phase

Max power (kW) | Max power (kVA) 5,7 kW | 7,1 kVA

75% Autonomy (h) 2,4

Sound power level guaranteed LwA dB(A) 97

Dimensions L x W x H (cm) | Weight (kg) 77 x 58 x 59 | 80

HX 7500 T C5 - GENERATING SET - INTENS - 6 février 2026

portable.rehlo.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

*This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.*



SDMO Industries
accredited testing laboratory ISO 17025
n°1-2171
scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	INTENS
Frequency (Hz)	50 Hz
Max power (kW)	5,7
Max power (kVA)	7,1
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Assigned current (A)	6,9
Tank (L)	6,1
75% cons. (l/h)	2,5
75% Autonomy (h)	2,4
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69



ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX390_C5
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	389
Oil system capacity including filters (l)	1,1



ALTERNATOR SPECIFICATION

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker



DIMENSIONS AND WEIGHT

Length (cm)	77
Width (cm)	58
Height (cm)	59
Dry Weight (kg)	80



PACKAGING

Packaging type	Box
Length (cm)	78,5
Width (cm)	58
Height (cm)	59,5
Weight (kg)	82,5
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	192
weight of the packaged Pallet (kg)	505

ACCESSORIES SUPPLIED



Funnel
User and maintenance manual

Additional equipment



3499231004012 VERSO 10 T 40A - Manual source inverter for connecting a three-phase generator to a house



RKB2

RKB2 - Trolley kit for HX 4000 - 6000 – 7500T / HXC 4000 - 6000 – 7500T / TECHNIC 10000 -15000 / VX 200/4 -220-7,5 / WELDARC 300 / TRASH ; Puncture-proof wheels Ø 290 mm



3499231033203 R19 - Maintenance kit for HX 6000 - 7500 T / VX 200/4 including oil, spark plug and air filter



RH1

RH1 - Protective cover for HX 4000 – 6000 – 7500T / HXC 4000 – 6000 – 7500T / PERFORM 4500 – 4500 XL – 5500T – 5500 T XL – 6500 – 6500 XL – 7500 T – 7500 XL / TECHNIC 6500 – 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm



RPM

RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket



RPQ

RPQ - 1m earth spike, supplied with 2m 10mm² mains cable



3499231920831

GSC - Generator Smart Care : Bluetooth box which can be used on all portable generator
