

WELDARC 220 T C5

EAN 3499231004128



PRODUCT ADVANTAGES

KOHLER air-cooled industrial engine
 Generating set guaranteed 3 years
 Good value for money
 Low consumption
 Light storage box integrated
 QUAD CLEAN AIR FILTER The Cyclonic Quad Clean air filters provide 4 levels of filtration which effectively filter out large particles and capture the finest particles. They ensure a continuous supply of clean air to the engine, fuel economies, increase the engine performance and extend its lifetime
 STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range

WELDARC INTENS
 Range provides a 2 in 1 generating set + welding set system, powerful and suitable for normal use.

Fuel Petrol

Nominal voltage (V) | Number of Phase 400 | Three phase

Normal duty cycle 35% (A) 200 A

Rods diameter maxi (mm) 4

75% Autonomy (h) 2,8

Sound power level guaranteed LwA dB(A) 99

Dimensions L x W x H (cm) | Weight (kg) 81 x 56,5 x 59 | 94,5



Attested NB 3065

WELDARC 220 T C5- WELDING SET - WELDARC INTENS - 6 février 2026

portable.rehlko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.



SDMO Industries
 accredited testing laboratory ISO 17025
 n°1-2171
 scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	WELDARC INTENS
Frequency (Hz)	50 Hz
Max power (kW)	5,7
Max power (kVA)	7,1
Normal duty cycle 35% (A)	200
Intensif duty cycle 60% (A)	170
Stricking volts (V)	73
Rods diameter mini (mm)	1.6
Rods diameter maxi (mm)	4
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Tank (L)	7,3
75% cons. (l/h)	2,6
75% Autonomy (h)	2,8
Sound power level guaranteed LwA dB(A)	99
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69



ENGINE SPECIFICATIONS

Engine brand	REHLKO
Engine ref.	CH440_C5
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	429
Oil system capacity including filters (l)	1,3



ALTERNATOR SPECIFICATION

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker



DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	56,5
Height (cm)	59
Dry Weight (kg)	94,5



PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56,5
Height (cm)	60
Weight (kg)	96,5
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	589

ACCESSORIES SUPPLIED



Funnel
User and maintenance manual

Additional equipment



3499231002575

RKB1HD - Trolley kit for PERFORM / PERFORM XL / TECHNIC 6500 - 7500T / DIESEL / WELDARC 200 - 220 ; Puncture-proof wheels Ø 290 mm



R10

R10 - Welding kit includes 1x10 m of cable, 1 earth clip, 1 electrode holder, 1 hammer, 1 brush and 1 mask (connectors not supplied).



3499231920039

RKS2 - Maintenance kit for PERFORM 4500 - 5500T – 6500 - 7500 T / WELDARC 200 - 220 T including oil, spark plug and air filter



RH1

RH1 - Protective cover for HX 4000 – 6000 – 7500T / HXC 4000 – 6000 – 7500T / PERFORM 4500 – 4500 XL – 5500T – 5500 T XL – 6500 – 6500 XL – 7500 T – 7500 XL / TECHNIC 6500 – 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm



RPQ

RPQ - 1m earth spike, supplied with 2m 10mm² mains cable



3499231920831

GSC - Generator Smart Care : Bluetooth box which can be used on all portable generator