

# DIESEL 6000 A SILENCE C5

EAN 3499231004197



## PRODUCT ADVANTAGES

Generating set guaranteed 3 years  
 KOHLER air-cooled industrial engine  
 Very Silent  
 Connection interface equipped with an hour meter  
 Hydrocarbons bulk tank  
 The GENERATOR SMART CARE is a Bluetooth box combined with a smartphone application that can be adapted to all the brand's portable generators and enables maintenance to be tracked.  
 The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature

## Range

**DIESEL SILENCE**  
 Performance and endurance combined with low noise to meet mobile and stationary applications.

**Fuel** Diesel Fuel

**Nominal voltage (V) | Number of Phase** 230 | Single phase

**Max power (kW)** 4,9 kW

**75% Autonomy (h)** 22,5

**Sound power level guaranteed LwA dB(A)** 92

**Dimensions L x W x H (cm) | Weight (kg)** 99 x 63 x 96 | 198



Attested NB 3065



Compatible

DIESEL 6000 A SILENCE C5 - GENERATING SET - DIESEL SILENCE - 6 février 2026

[portable.rehlko.com](http://portable.rehlko.com)

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

*This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.*



**SDMO Industries**  
 accredited testing laboratory ISO 17025  
 n°1-2171  
 scope available on [www.cofrac.fr](http://www.cofrac.fr)





## GENERAL SPECIFICATIONS

<b>Range</b>	DIESEL SILENCE
<b>Frequency (Hz)</b>	50 Hz
<b>Max power (kW)</b>	4,9
<b>Nominal voltage (V)</b>	230
<b>Number of Phase</b>	Single phase
<b>Assigned current (A)</b>	18,1
<b>Fuel</b>	Diesel Fuel
<b>Tank (L)</b>	27
<b>75% cons. (l/h)</b>	1,2
<b>75% Autonomy (h)</b>	22,5
<b>Sound power level guaranteed LwA dB(A)</b>	92
<b>Acoustic pressure level @1m in dB(A)</b>	76
<b>Acoustic pressure level @7m in dB(A)</b>	63



## ENGINE SPECIFICATIONS

<b>Engine brand</b>	REHLKO
<b>Engine ref.</b>	KD15-440E_C5
<b>Start</b>	Electrical
<b>Oil shutdown</b>	Oui
<b>Displacement (cm3)</b>	440
<b>Oil system capacity including filters (l)</b>	1,5



## ALTERNATOR SPECIFICATION

<b>Technology</b>	Brushless
<b>AVR Regulation</b>	No
<b>Indication of protection</b>	IP 23
<b>Insulation class</b>	H



## PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 230V 32A socket - circuit breaker + hour meter + indicator + APM202



## DIMENSIONS AND WEIGHT

<b>Length (cm)</b>	99
<b>Width (cm)</b>	63
<b>Height (cm)</b>	96
<b>Dry Weight (kg)</b>	198



## PACKAGING

<b>Packaging type</b>	Box
<b>Length (cm)</b>	101
<b>Width (cm)</b>	63
<b>Height (cm)</b>	94
<b>Weight (kg)</b>	201
<b>Pallet type</b>	
<b>Number of box by pallet</b>	0
<b>Pallet height (cm)</b>	0
<b>weight of the packaged Pallet (kg)</b>	0

## ACCESSORIES SUPPLIED



User and maintenance manual  
 Battery without maintenance  
 Lifting eye  
 Hour meter

## Additional equipment



**3499231002834** RSTART2 - Wireless remote control with on/off button. Requires a genset fitted with an APM202/APM303

---



**3499231001110** VERSO 50 Mono 40A - Automatic source inverter on 40A single-phase mains failure (includes battery charger) for an installation of up to 9.2kW. Requires a genset fitted with an APM202/APM303

---



**R05M** R05M - Manual transfer switch for connecting a single-phase generator to a house

---



**3499231000816** RKB3 - Trolley kit for DIESEL 6000 A SILENCE / 6500 TA SILENCE ; Puncture-proof wheels Ø 290 mm

---



**3499231004548** RKDS5 - Maintenance kit for DIESEL 6000 SILENCE - 6500 SILENCE including oil filter, fuel prefilter, fuel filter and air filter

---



**3499231002827** RAP - Adapter from 16A industrial socket to 10/16A domestic socket

---



**RPM** RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket

---



**RPQ** RPQ - 1m earth spike, supplied with 2m 10mm<sup>2</sup> mains cable

---