

DIESEL 4000 E XL C5

EAN 3499231004302



PRODUCT ADVANTAGES

Generating set guaranteed 3 years
 KOHLER air-cooled industrial engine
 Large Autonomy
 Comfort of prehension thanks to the ergonomic handles
 Electric starter with batteries without maintenance
 The GENERATOR SMART CARE is a Bluetooth box combined with a smartphone application that can be adapted to all the brand's portable generators and enables maintenance to be tracked.
 STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range

DIESEL
 Both long run times and very long life for professional applications.

Fuel Diesel Fuel

Nominal voltage (V) | Number of Phase 230 | Single phase

Max power (kW) 3,4 kW

75% Autonomy (h) 17,8

Sound power level guaranteed LwA dB(A) 108

Dimensions L x W x H (cm) | Weight (kg) 81 x 56,5 x 59 | 84



Attested NB 3065



Compatible

DIESEL 4000 E XL C5 - GENERATING SET - DIESEL - 6 février 2026

portable.rehlo.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.



SDMO Industries
 accredited testing laboratory ISO 17025
 n°1-2171
 scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	DIESEL
Frequency (Hz)	50 Hz
Max power (kW)	3,4
Nominal voltage (V)	230
Number of Phase	Single phase
Assigned current (A)	11,8
Fuel	Diesel Fuel
Tank (L)	16
75% cons. (l/h)	0,9
75% Autonomy (h)	17,8
Sound power level guaranteed LwA dB(A)	108
Acoustic pressure level @1m in dB(A)	92
Acoustic pressure level @7m in dB(A)	78



ENGINE SPECIFICATIONS

Engine brand	REHLKO
Engine ref.	KD350E_C5
Start	Electrical
Oil shutdown	Oui
Displacement (cm3)	349
Oil system capacity including filters (l)	1,2



ALTERNATOR SPECIFICATION

Technology	Brushless
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker



DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	56,5
Height (cm)	59
Dry Weight (kg)	84



PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56,5
Height (cm)	60
Weight (kg)	87
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	532

ACCESSORIES SUPPLIED



User and maintenance manual
 Floor maintaining slot
 Ergonomic handle grip

Additional equipment



R05M

R05M - Manual transfert switch for connecting a single-phase generator to a house



3499231001745

RKDS1 - Maintenance kit for DIESEL 4000 / TRASH 3 / TRASH 4 including oil filter, fuel filter and air filter



RH1

RH1 - Protective cover for HX 4000 – 6000 – 7500T / HXC 4000 – 6000 – 7500T / PERFORM 4500 – 4500 XL – 5500T – 5500 T XL – 6500 – 6500 XL – 7500 T – 7500 XL / TECHNIC 6500 – 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm



RPM

RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket



RPQ

RPQ - 1m earth spike, supplied with 2m 10mm² mains cable



RKD1

RKD1 - Kit of 2 removable differential adaptors for domestic sockets 16A
