

# DIESEL 10000 A XL - STAND BY

EAN 3499231004609



## PRODUCT ADVANTAGES

Generating set guaranteed 3 years  
 KOHLER air-cooled industrial engine  
 Electric starter with batteries without maintenance  
 Connection interface equipped with an hour meter  
 Large Autonomy  
 The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature  
 OIL SAFETY Thanks to this functionality, the engine will not start or will stop during its functioning if the oil level for gasolines or the oil pression for diesels is to low : your generating set is perfectly protected !

## Range

DIESEL  
 Both long run times and very long life for professional applications.

**Fuel** Diesel Fuel

**Nominal voltage (V) | Number of Phase** 230 | Single phase

**Max power (kW)** 9 kW

**75% Autonomy (h)** 16,7

**Sound power level guaranteed LwA dB(A)** 109

**Dimensions L x W x H (cm) | Weight (kg)** 89,5 x 58,5 x 77 | 162



Compatible

DIESEL 10000 A XL - STAND BY - GENERATING SET - DIESEL - 6 février 2026

[portable.rehlko.com](http://portable.rehlko.com)

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.





## GENERAL SPECIFICATIONS

<b>Range</b>	DIESEL
<b>Frequency (Hz)</b>	50 Hz
<b>Max power (kW)</b>	9
<b>Nominal voltage (V)</b>	230
<b>Number of Phase</b>	Single phase
<b>Assigned current (A)</b>	31,3
<b>Fuel</b>	Diesel Fuel
<b>Tank (L)</b>	35
<b>75% cons. (l/h)</b>	2,1
<b>75% Autonomy (h)</b>	16,7
<b>Sound power level guaranteed LwA dB(A)</b>	109
<b>Acoustic pressure level @1m in dB(A)</b>	95
<b>Acoustic pressure level @7m in dB(A)</b>	80



## ENGINE SPECIFICATIONS

<b>Engine brand</b>	REHLKO
<b>Engine ref.</b>	KD425-2
<b>Start</b>	Electrical
<b>Oil shutdown</b>	Oui
<b>Displacement (cm3)</b>	850
<b>Oil system capacity including filters (l)</b>	2,6



## ALTERNATOR SPECIFICATION

<b>Technology</b>	Brushless
<b>AVR Regulation</b>	No
<b>Indication of protection</b>	IP 23
<b>Insulation class</b>	H



## PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 230V 32A socket - circuit breaker + hour meter + indicator + APM202



## DIMENSIONS AND WEIGHT

<b>Length (cm)</b>	89,5
<b>Width (cm)</b>	58,5
<b>Height (cm)</b>	77
<b>Dry Weight (kg)</b>	162



## PACKAGING

<b>Packaging type</b>	Box / Pallet
<b>Length (cm)</b>	91
<b>Width (cm)</b>	58,5
<b>Height (cm)</b>	92
<b>Weight (kg)</b>	175
<b>Pallet type</b>	
<b>Number of box by pallet</b>	0
<b>Pallet height (cm)</b>	0
<b>weight of the packaged Pallet (kg)</b>	0

## ACCESSORIES SUPPLIED



User and maintenance manual

## Additional equipment



**3499231002834** RSTART2 - Wireless remote control with on/off button. Requires a genset fitted with an APM202/APM303

---



**3499231001110** VERSO 50 Mono 40A - Automatic source inverter on 40A single-phase mains failure (includes battery charger) for an installation of up to 9.2kW. Requires a genset fitted with an APM202/APM303

---



**R05M** R05M - Manual transfer switch for connecting a single-phase generator to a house

---



**3499231001776** RKDS3 - Maintenance kit for DIESEL 10000 XL STAND BY / DIESEL 15000 including oil filter, fuel filter and air filter

---



**3499231002827** RAP - Adapter from 16A industrial socket to 10/16A domestic socket

---



**RH2** RH2 - Protective cover for TECHNIC 10000 – 15000 / DIESEL 10000 A XL STAND BY – 15000 TA XL ;  
Dimensions : 91 x 58 x 56 cm

---



**RPM** RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket

---



**RPQ** RPQ - 1m earth spike, supplied with 2m 10mm<sup>2</sup> mains cable

---