

# DIESEL 15000 TA XL - STAND BY

EAN 3499231004616



## PRODUCT ADVANTAGES

Generating set guaranteed 3 years  
 KOHLER air-cooled industrial engine  
 Electric starter with batteries without maintenance  
 Connection interface equipped with an hour meter  
 Large Autonomy  
 The APM202 control panel displays overspeed, starting failure, oil pressure, battery and temperature  
 OIL SAFETY Thanks to this functionality, the engine will not start or will stop during its functioning if the oil level for gasolines or the oil pressure for diesels is too low : your generating set is perfectly protected !

## Range

DIESEL  
 Both long run times and very long life for professional applications.

Fuel Diesel Fuel

Nominal voltage (V) | Number of Phase 400 | Three phase

Max power (kW) | Max power (kVA) 10 kW | 12,5 kVA

75% Autonomy (h) 16,7

Sound power level guaranteed LwA dB(A) 109

Dimensions L x W x H (cm) | Weight (kg) 89,5 x 58,5 x 77 | 169



DIESEL 15000 TA XL - STAND BY - GENERATING SET - DIESEL - 6 février 2026

[portable.rehlko.com](http://portable.rehlko.com)

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.



SDMO Industries  
 accredited testing laboratory ISO 17025  
 n°1-2171  
 scope available on [www.cofrac.fr](http://www.cofrac.fr)





## GENERAL SPECIFICATIONS

Range	DIESEL
Frequency (Hz)	50 Hz
Max power (kW)	10
Max power (kVA)	12,5
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Diesel Fuel
Assigned current (A)	11,6
Tank (L)	35
75% cons. (l/h)	2,1
75% Autonomy (h)	16,7
Sound power level guaranteed LwA dB(A)	109
Acoustic pressure level @1m in dB(A)	95
Acoustic pressure level @7m in dB(A)	80



## ENGINE SPECIFICATIONS

Engine brand	REHLKO
Engine ref.	KD425-2
Start	Electrical
Oil shutdown	Oui
Displacement (cm3)	850
Oil system capacity including filters (l)	2,6



## ALTERNATOR SPECIFICATION

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H



## PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 16A socket - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter + indicator + APM202



## DIMENSIONS AND WEIGHT

Length (cm)	89,5
Width (cm)	58,5
Height (cm)	77
Dry Weight (kg)	169



## PACKAGING

Packaging type	Box / Pallet
Length (cm)	91
Width (cm)	58,5
Height (cm)	92
Weight (kg)	182
Pallet type	
Number of box by pallet	0
Pallet height (cm)	0
weight of the packaged Pallet (kg)	0

## ACCESSORIES SUPPLIED



User and maintenance manual

## Additional equipment



**3499231002834** RSTART2 - Wireless remote control with on/off button. Requires a genset fitted with an APM202/APM303

---



**3499231001134** VERSO 50 Tri 25 A - Automatic source inverter on 25A three-phase mains failure (includes battery charger) for an installation of up to 10 KVA. Requires a genset fitted with an APM202/APM303

---



**3499231004012** VERSO 10 T 40A - Manual source inverter for connecting a three-phase generator to a house

---



**3499231001776** RKDS3 - Maintenance kit for DIESEL 10000 XL STAND BY / DIESEL 15000 including oil filter, fuel filter and air filter

---



**3499231002827** RAP - Adapter from 16A industrial socket to 10/16A domestic socket

---



**RH2** RH2 - Protective cover for TECHNIC 10000 – 15000 / DIESEL 10000 A XL STAND BY – 15000 TA XL ;  
Dimensions : 91 x 58 x 56 cm

---



**RPM** RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket

---



**RPQ** RPQ - 1m earth spike, supplied with 2m 10mm<sup>2</sup> mains cable

---