

ST 2.38 C5

EAN 3499231037003



PRODUCT ADVANTAGES

HONDA Professional Engine
Automatic priming
Offers accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

Range

AQUALINE INTENS
Designed for water with low solid content.

	Fuel	Petrol
	Granulometry (mm)	8
	Type liquid	Clear water with little sediment pump
	Lifting height (m)	27
	Outflow maximum (m ³ /h)	38
	75% Autonomy (h)	3,4
	Sound power level guaranteed LwA dB(A)	104
	Dimensions L x W x H (cm) Weight (kg)	50,5 x 42,9 x 44,8 26,5

ST 2.38 C5 - WATER PUMP - AQUALINE INTENS - 6 février 2026

portable.rehiko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.



SDMO Industries
accredited testing laboratory ISO 17025
n°1-2171
scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Clear water with little sediment
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (m3/h)	38
Outflow maximum (L/min)	640
Lifting height (m)	27
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Oui
Fuel	Petrol
Tank (L)	3,1
75% cons. (l/h)	0,9
75% Autonomy (h)	3,4
Sound power level guaranteed LwA dB(A)	104
Acoustic pressure level @1m in dB(A)	90
Acoustic pressure level @7m in dB(A)	75



ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160_C5
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (l)	0,6



DIMENSIONS AND WEIGHT

Length (cm)	50,5
Width (cm)	42,9
Height (cm)	44,8
Dry Weight (kg)	26,5



PACKAGING

Packaging type	Box
Length (cm)	52
Width (cm)	42,9
Height (cm)	46,3
Weight (kg)	29,3
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	152
weight of the packaged Pallet (kg)	361,6

ACCESSORIES SUPPLIED



Inlet filter
Circlips
Screw-on connectors
User and maintenance manual

Additional equipment



3499231921463

RKS13 - Maintenance kit for ST 2.38 / ST 3.60/ TR 2.35 / TR 2.60 / HP 2.26 / XT 3.78 including oil, spark plug and air filter



3499231036006

GENLUB 15W40 1L - Oil can 1L (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



3499231035009

GENLUB 15W40 0.5L - Oil can 0.5L (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



RHO

RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm



R11

R11 - Piping kit for 2 inches water pumps made up of 5m suction + 25m lift



R13

R13 - Rapid connections kit for 2 inches water pumps
