

# TR 2.35 C5

EAN 3499231037010



## PRODUCT ADVANTAGES

HONDA Professional Engine  
Resistant pump-barrel  
Automatic priming  
Easy access to the turbine  
Offers accessories

STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

## Range

AQUALINE INTENS  
Designed for water with low solid content.

	Fuel	Petrol
	Granulometry (mm)	8
	Type liquid	Heavily sedimented water pump
	Lifting height (m)	26
	Outflow maximum (m3/h)	35
	75% Autonomy (h)	3,4
	Sound power level guaranteed LwA dB(A)	104
	Dimensions L x W x H (cm)   Weight (kg)	50,5 x 42,9 x 46,6   28,7

TR 2.35 C5 - WATER PUMP - AQUALINE INTENS - 6 février 2026

[portable.rehiko.com](http://portable.rehiko.com)

SDMO Industries - 270 rue de Kervern - CS 40047 - 29801 Brest cedex 9 – France

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.



**SDMO Industries**  
accredited testing laboratory ISO 17025  
n°1-2171  
scope available on [www.cofrac.fr](http://www.cofrac.fr)






## GENERAL SPECIFICATIONS

<b>Range</b>	AQUALINE INTENS
<b>Type liquid</b>	Heavily sedimented water pump
<b>Suction diameter [mm]</b>	50
<b>Backflow diameter (mm)</b>	50
<b>Outflow maximum (m3/h)</b>	35
<b>Outflow maximum (L/min)</b>	580
<b>Lifting height (m)</b>	26
<b>Suction height (m)</b>	8
<b>Granulometry (mm)</b>	8
<b>Automatic priming</b>	Oui
<b>Fuel</b>	Petrol
<b>Tank (L)</b>	3,1
<b>75% cons. (l/h)</b>	0,9
<b>75% Autonomy (h)</b>	3,4
<b>Sound power level guaranteed LwA dB(A)</b>	104
<b>Acoustic pressure level @1m in dB(A)</b>	90
<b>Acoustic pressure level @7m in dB(A)</b>	75



## ENGINE SPECIFICATIONS

<b>Engine brand</b>	HONDA
<b>Engine ref.</b>	GX160_C5
<b>Start</b>	Starter
<b>Oil shutdown</b>	Oui
<b>Displacement (cm3)</b>	163
<b>Oil system capacity including filters (l)</b>	0,6



## DIMENSIONS AND WEIGHT

<b>Length (cm)</b>	50,5
<b>Width (cm)</b>	42,9
<b>Height (cm)</b>	46,6
<b>Dry Weight (kg)</b>	28,7



## PACKAGING

<b>Packaging type</b>	Box
<b>Length (cm)</b>	52
<b>Width (cm)</b>	42,9
<b>Height (cm)</b>	47,8
<b>Weight (kg)</b>	31
<b>Pallet type</b>	120/80
<b>Number of box by pallet</b>	12
<b>Pallet height (cm)</b>	156
<b>weight of the packaged Pallet (kg)</b>	382

## ACCESSORIES SUPPLIED



Inlet filter  
Circlips  
Screw-on connectors  
User and maintenance manual

## Additional equipment



3499231921463

RKS13 - Maintenance kit for ST 2.38 / ST 3.60/ TR 2.35 / TR 2.60 / HP 2.26 / XT 3.78 including oil, spark plug and air filter



3499231036006

GENLUB 15W40 1L - Oil can 1L (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



3499231035009

GENLUB 15W40 0.5L - Oil can 0.5L (15W40) for INVERTER / PERFORM / PERFORM XL / HX / TECHNIC 6500 - 7500 / DIESEL 4000 / WELDARC 200 / VX 200/4 / AQUALINE



RHO

RHO - Protective cover for HX 3000 / HXC 3000 / PERFORM 3000 - 3000 XL / PRESTIGE 3000 / ST 2,36 - 3,60 / TR 2,36 - 3,60 / HP 2,26 / XT 3,78 ; Dimensions : 70 x 45 x 50 cm



R11

R11 - Piping kit for 2 inches water pumps made up of 5m suction + 25m lift



R13

R13 - Rapid connections kit for 2 inches water pumps