

PERFORM 6500 XL C5

EAN 3499231921180



PRODUCT ADVANTAGES

Compact frame with protection panels against shocks
 Starting up facilitated thanks to the summer/winter positions
 KOHLER air-cooled industrial engine
 Good value for money
 Generating set guaranteed 3 years
 STAGE V (2016/1628 EU) : This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe
 OVERSIZED ALTERNATOR The oversized alternator is ideal for supplying electronic equipment and secures the engines supplying . It has very low harmonic current and limits the voltage and frequency variation of the power supplied as well as handling high surge loads.

Range

PERFORM XL

An efficient, cost effective and easy to handle equipment, suitable for frequent use.

Fuel Petrol

Nominal voltage (V) | Number of Phase 230 | Single phase

Max power (kW) 6,3 kW

75% Autonomy (h) 6,9

Sound power level guaranteed LwA dB(A) 97

Dimensions L x W x H (cm) | Weight (kg) 81 x 56,5 x 59 | 91,5



PERFORM 6500 XL C5 - GENERATING SET - PERFORM XL - 6 février 2026

portable.rehlko.com

SDMO Industries - 270 rue de Kerervern - CS 40047 - 29801 Brest cedex 9 – France

*This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.*



SDMO Industries
 accredited testing laboratory ISO 17025
 n°1-2171
 scope available on www.cofrac.fr





GENERAL SPECIFICATIONS

Range	PERFORM XL
Frequency (Hz)	50 Hz
Max power (kW)	6,3
Nominal voltage (V)	230
Number of Phase	Single phase
Assigned current (A)	20,9
Fuel	Petrol
Tank (L)	18
75% cons. (l/h)	2,6
75% Autonomy (h)	6,9
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	83
Acoustic pressure level @7m in dB(A)	69



ENGINE SPECIFICATIONS

Engine brand	REHLKO
Engine ref.	CH440_C5
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	429
Oil system capacity including filters (l)	1,3



ALTERNATOR SPECIFICATION

Technology	Brushless
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H



PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 230V 32A socket- circuit breaker



DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	56,5
Height (cm)	59
Dry Weight (kg)	91,5



PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56,5
Height (cm)	60
Weight (kg)	93,5
Pallet type	120/80
Number of box by pallet	4
Pallet height (cm)	133
weight of the packaged Pallet (kg)	384

ACCESSORIES SUPPLIED



Funnel
 User and maintenance manual
 Floor maintaining slot
 Ergonomic handle grip

Additional equipment



R05M

R05M - Manual transfert switch for connecting a single-phase generator to a house



3499231002575

RKB1HD - Trolley kit for PERFORM / PERFORM XL / TECHNIC 6500 - 7500T / DIESEL / WELDARC 200 - 220 ; Puncture-proof wheels Ø 290 mm



3499231005057

RKS7 - Maintenance kit for PERFORM 4500 XL - 5500T XL - 6500 XL - 7500T XL / TECHNIC 6500 - 7500T including oil, spark plug, fuel filter and air filter



RH1

RH1 - Protective cover for HX 4000 – 6000 – 7500T / HXC 4000 – 6000 – 7500T / PERFORM 4500 – 4500 XL – 5500T – 5500 T XL – 6500 – 6500 XL – 7500 T – 7500 XL / TECHNIC 6500 – 7500 TE / DIESEL / TRASH ; Dimensions : 82 x 58 x 50 cm



RPM

RPM - Plug kit for all models: 2 x 16A /230V sockets, 1 x CEE17 16A/230V socket, 1 x 32A/230V socket, 1 x 16A/400V socket



RPQ

RPQ - 1m earth spike, supplied with 2m 10mm² mains cable



3499231920831

GSC - Generator Smart Care : Bluetooth box which can be used on all portable generator
